

INDUSTRIAL ENGINES

› 6491 - DRLB (4.9L 6 CYLINDER)
GEN II DRESSED ENGINE



STANDARD FEATURES:

- Log Style Industrial In-Take & Exhaust Manifolds
- Complete Ignition System with distributor, coil, wires, plugs, ICM, and resistor
- 65 - AMP Alternator mounted with dual pulley & belts
- 12V Starter shipped loose
- High Flow Water Pump with dual groove pulley
- Standard Breakerless Ignition System
- OEM Type Thermostat Housing with fail safe thermostat
- Dual V - Belt Harmonic Balancer
- Heavy Gauge Engine Sheet Metal included
- All Engines are Dyno Tested over the entire RPM range to guarantee proper function before oil is drained prior to shipping.

SPECIFICATIONS:

Engine type *Inline 6 cylinder*
Bore & stroke.....4.03" x 3.98" (102.1 101.1mm)
Displacement.....4.98L (305 CID)
Compression ratio9.0:1
Oil capacity7qts. (6.6Ltr's) including filter
New weight.....437 lbs. (215 kgs.)
Fuel.....Gasoline, 87 A.K.I.
Optional use of.....LPG, NG & other fuel blends

* Specifications subject to change without notice.

MORE REASONS TO CHOOSE RMP AS YOUR SOURCE FOR POWER:

1. Gen II block features + .030 Bore and - .010 rod & mains. All other items are new.
2. Only RMP offers a dressed 4.9L engine suitable for use in the ground support & other industrial markets.
3. All 4.9L engines are test ran under load at our in - house dyno testing facility.
4. Gen II engines feature a 12 month limited warranty.
5. Service is supported by a nation - wide network of dealers & distributors.

TYPICAL PUMP GASOLINE POWER RATINGS:

Rated power @ 3600 RPM Intermittent: 125HP (93kW)
| Continuous: 102 HP (75 kW)

Peak Torque @ 2000 RPM
(328 Nm) | Continuous: 205 Ft. Lbs. (277 Nm)

 **800 257 7418**
find, friend, follow...
powertrainsolutions.com 